



With its deep understanding of set top box design, WCD1210 has been designed to cater to MSO's requirement for a low-cost product without any compromise on quality. With improved stability and multiple new features, WCD1210 provides more options for operators to customize for their unique environments.

Features

- Fully MPEG-4, H.264, HD Digital and DVB-C compliant
- HD Video Resolution upto 1080p
- Multi-languages EPG, teletext and subtitle support
- USB PVR and Time-shift function
- Four search modes: Manual/NIT/All Frequency/Advanced
- 8 favorite channel groups settings, 10 timers settings and parental lock function
- OTA update
- Advertising Insertion option

Specifications

PROCESSOR & MEMORY	
Chipset	ALI M3812
Flash Memory	8 MB
RAM	128 MB
DVB-C INPUT	
Input Signal Level	36-100 dBuV (64 QAM)
Input Symbol Rate	3.0-6.952 Ms/S
Input Frequency	47-862 MHz
Input Impedance	75 ohm
Demodulator	16/32/64/128/256 QAM
VIDEO PROCESSING	
Video Decoding	MPEG-4 AVC/H.264 MP@L4.1, MPEG-2 MP@HL
AUDIO PROCESSING	
Audio Decoding	AAC, MPEG1/2 layer I&II, AC-3 (license)
Sound Mode	Stereo, Mono
A/V output	Phone Jack x 1, HDMI x 1
SIZE & WEIGHT	
Net Wt. = 165 gms	Dims : 130 x 115 x 35 mm

REAR PANEL	
Video Out	HDMI: 1080p/720p/576p/480p/480i
Video & Audio Out	1 x 3.5mm Jack (TRRS) for CVBS:576i(PAL) and Stereo (L & R) Audio Output
RF In & Out	ICE, RF Out is Loop-through
USB (PVR Function)	USB (2.0 Host)
RCU	
Category	IR (Carrier 38 KHz)
Batteries	2 x 1.5V (AAA)
POWER	
Ext. Adapter	Input : 90-270 Vac Output : 5V DC, 2A
Standby Consumption	< 2W
Operating Temperature	0 - 50 °C

